ECODESIGN INFORMATION

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

a) fan type
b) fan efficiency [%]
c) VSD assumed in data
d) Measurement category
e) Efficiency category
f) N fan
g1) Pe [kW]
g2) qv [m³/h]
g3) Δp [Pa]
h1) dual use fan
h2) reversible fan
h3) low noise fan
i) DC voltage lower than 100 V
k) σBEP
l) fan speed [rpm]
m) specific ratio
j) p) q) significant elements, disassembly and recycling info on product manual

Model	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
CBD-1919-4M 1/5 3V	forward curved centrifugal fan	33.5	VSD not necessary	A	Static	52.1	0.170	968	211	No	No	No	No	0.00	1230	1.00
CBD-2525-4M 3/4 3V	forward curved centrifugal fan	41.2	VSD not necessary	C	Static	53.9	0.619	2620	351	No	No	No	No	0.00	1310	1.00
CBD-2525-6M 1/3 3V	forward curved centrifugal fan	40.4	VSD not necessary	B	Total	57.2	0.252	2136	171	No	No	No	No	0.00	830	1.00
CBD-2828-4M 3/4 3V	forward curved centrifugal fan	44.8	VSD not necessary	C	Static	56.8	0.713	3123	368	No	No	No	No	0.00	1310	1.00
CBD-2828-6M 1/3 3V	forward curved centrifugal fan	42.7	VSD not necessary	C	Static	58.9	0.282	2302	188	No	No	No	No	0.00	830	1.00
CBD-2828-6M 3/4 3V	forward curved centrifugal fan	37.9	VSD not necessary	C	Static	53.1	0.352	2539	189	No	No	No	No	0.00	850	1.00
CBD-3333-6M 1 3V	forward curved centrifugal fan	46.3	VSD not necessary	C	Static	58.3	0.723	4433	272	No	No	No	No	0.00	850	1.00