

ECODESIGN INFORMATION

www.sodeca.com

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

- a) fan type

b) fan efficiency [%]

c) VSD assumed in data

d) Measurement category
- e) Efficiency category

f) N fan

g1) Pe [kW]

g2) qv [m³/h]
- g3) Δp [Pa]

h1) dual use fan

h2) reversible fan

h3) low noise fan
- i) DC voltage lower than 100 V

k) σBEP

l) fan speed [rpm]

m) specific ratio
- j) p) q) significant elements, disassembly and recycling info on product manual

Model	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
CMPH-512-2T-0.25								Exclude. Gas Temp> 100°C								
CMPH-512-4T-0.16								Exclude. Gas Temp> 100°C								
CMPH-514-2T-0.25								Exclude. Gas Temp> 100°C								
CMPH-514-4T-0.16								Exclude. Gas Temp> 100°C								
CMPH-616-2T-0.5								Exclude. Gas Temp> 100°C								
CMPH-616-4T-0.16								Exclude. Gas Temp> 100°C								
CMPH-620-2T-0.5								Exclude. Gas Temp> 100°C								
CMPH-620-4T-0.16								Exclude. Gas Temp> 100°C								
CMPH-718-2T-1 IE3								Exclude. Gas Temp> 100°C								
CMPH-718-4T-0.33								Exclude. Gas Temp> 100°C								
CMPH-820-2T-1.5 IE3								Exclude. Gas Temp> 100°C								
CMPH-820-4T-0.33								Exclude. Gas Temp> 100°C								
CMPH-922-2T-1.5 IE3								Exclude. Gas Temp> 100°C								
CMPH-922-2T-2 IE3								Exclude. Gas Temp> 100°C								
CMPH-922-2T-3 IE3								Exclude. Gas Temp> 100°C								
CMPH-922-4T-0.75								Exclude. Gas Temp> 100°C								
CMPH-1025-2T-3 IE3								Exclude. Gas Temp> 100°C								
CMPH-1025-2T-4 IE3								Exclude. Gas Temp> 100°C								
CMPH-1025-4T-1.5 IE3								Exclude. Gas Temp> 100°C								
CMPH-1128-2T-4 IE3								Exclude. Gas Temp> 100°C								
CMPH-1128-2T-5.5 IE3								Exclude. Gas Temp> 100°C								
CMPH-1128-4T-3 IE3								Exclude. Gas Temp> 100°C								
CMPH-1128-6T-1 IE3								Exclude. Gas Temp> 100°C								
CMPH-1231-4T-3 IE3								Exclude. Gas Temp> 100°C								
CMPH-1231-4T-4 IE3								Exclude. Gas Temp> 100°C								
CMPH-1231-4T-5.5 IE3								Exclude. Gas Temp> 100°C								
CMPH-1231-6T-2 IE3								Exclude. Gas Temp> 100°C								
CMPH-1435-4T-4 IE3								Exclude. Gas Temp> 100°C								
CMPH-1435-4T-5.5 IE3								Exclude. Gas Temp> 100°C								
CMPH-1435-4T-7.5 IE3								Exclude. Gas Temp> 100°C								
CMPH-1435-6T-3 IE3								Exclude. Gas Temp> 100°C								
CMPH-1640-4T-5.5 IE3								Exclude. Gas Temp> 100°C								
CMPH-1640-4T-7.5 IE3								Exclude. Gas Temp> 100°C								
CMPH-1640-4T-10 IE3								Exclude. Gas Temp> 100°C								
CMPH-1640-6T-3 IE3								Exclude. Gas Temp> 100°C								
CMPH-1845-4T-7.5 IE3								Exclude. Gas Temp> 100°C								

ECODESIGN INFORMATION

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

Model	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
CMPH-1845-4T-10 IE3																
CMPH-1845-6T-3 IE3																
CMPH-2050-4T-10 IE3																
CMPH-2050-4T-15 IE3																
CMPH-2050-4T-20 IE3																
CMPH-2050-6T-5.5 IE3																
CMPH-2563-6T-15 IE3																
CMPH-2563-6T-25 IE3																