

# ECODESIGN INFORMATION

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

- a) fan type

b) fan efficiency [%]

c) VSD assumed in data

d) Measurement category
- e) Efficiency category

f) N fan

g1) Pe [kW]

g2) qv [m³/h]
- g3) Δp [Pa]

h1) dual use fan

h2) reversible fan

h3) low noise fan
- i) DC voltage lower than 100 V

k) σBEP

l) fan speed [rpm]

m) specific ratio
- j) p) q) significant elements, disassembly and recycling info on product manual

| Model              | a) | b) | c) | d) | e) | f) | g1) | g2) | g3) | h1) | h2) | h3) | i) | k) | l) | m)                       |
|--------------------|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|----|----|----|--------------------------|
| HBA-31-2T-0.75     |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-31-2M-0.75     |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-31-4T-0.37     |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-31-4M-0.37     |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-40-2T-1.5 IE3  |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-40-2M-1.5      |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-40-4T-0.5      |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-45-2T-4 IE3    |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-50-4T-1 IE3    |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-63-4T-1.5 IE3  |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-71-4T-5.5 IE3  |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-71-6T-0.75     |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-80-6T-1.5 IE3  |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |
| HBA-100-6T-1.5 IE3 |    |    |    |    |    |    |     |     |     |     |     |     |    |    |    | Exclude. Gas Temp> 100°C |