

# ECODESIGN INFORMATION

www.sodeca.com

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

- a) fan type

b) fan efficiency [%]

c) VSD assumed in data

d) Measurement category
- e) Efficiency category

f) N fan

g1) Pe [kW]

g2) qv [m³/h]
- g3) Δp [Pa]

h1) dual use fan

h2) reversible fan

h3) low noise fan
- i) DC voltage lower than 100 V

k) σBEP

l) fan speed [rpm]

m) specific ratio
- j) p) q) significant elements, disassembly and recycling info on product manual

| Model             | a)                       | b) | c) | d) | e) | f) | g1) | g2) | g3) | h1) | h2) | h3) | i) | k) | l) | m) |
|-------------------|--------------------------|----|----|----|----|----|-----|-----|-----|-----|-----|-----|----|----|----|----|
| HPX-35-2T-0.75    | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-35-4T-0.33    | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-45-4T-0.33    | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-45-4T-0.50    | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-50-4T-0.75    | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-50-4T-1 IE3   | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-56-4T-0.75    | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-56-4T-1 IE3   | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-56-4T-1.5 IE3 | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-63-4T-1.5 IE3 | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-63-4T-2 IE3   | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-71-4T-1.5 IE3 | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-71-4T-2 IE3   | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-71-4T-3 IE3   | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-80-4T-4 IE3   | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-80-4T-5.5 IE3 | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-90-4T-5.5 IE3 | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-90-4T-7.5 IE3 | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-100-4T-10 IE3 | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |
| HPX-100-4T-15 IE3 | Exclude. Gas Temp> 100°C |    |    |    |    |    |     |     |     |     |     |     |    |    |    |    |